



**CATALYST CAMPUS  
METAL STUD FRAMING & DRYWALL**

| Item # | Scope of Work                            | Qty +/- | Type | Amount | Notes   |
|--------|--|---------|------|--------|---|
| 1      | Mobilizations                            | 1       | LOT  |        | It is assumed for this scope of work, multiple mobilizations will be required throughout the course of the project. |
| 2      | 3'-0" X 7'-0" Solid Wood Core & HM Frame | 8       | EA   |        |   |
| 3      | 3'-6" X 7'-0" Solid Wood Core & HM Frame | 2       | EA   |        |   |
| 4      | Hardware                                 | 12      | SETS |        |   |
| 5      | Install of Doors & Hardware              | 10      | EA   |        |   |
| 6      | <b>TYPE 1, GWB WALL (11 LF)</b>          |         |      |        |   |
| 7      | (3-5/8") Metal stud @ 16" O.C            | 120     | LF   |        |   |
| 8      | (5/8", 1-Layer) Gyp. Bd. One side.       | 140     | SF   |        |   |
| 9      | (3-5/8") Top & bottom track.             | 22      | LF   |        |   |
| 10     | Acoustic sealant.                        | 11      | LF   |        |   |
| 11     | <b>TYPE 2, GWB WALL (39 LF)</b>          |         |      |        |   |
| 12     | (3-5/8") Metal stud @ 16" O.C            | 150     | LF   |        |   |
| 13     | (3-1/2") Sound attenuation insulation.   | 175     | SF   |        |   |
| 14     | (5/8", 1-Layer) Gyp. Bd. one side.       | 175     | SF   |        |   |
| 15     | (3-5/8") Top & bottom track.             | 78      | LF   |        |   |
| 16     | Acoustic sealant.                        | 39      | LF   |        |   |
| 17     | <b>TYPE 3, GWB WALL (5 LF)</b>           |         |      |        |   |
| 18     | (3-5/8") Metal stud @ 16" O.C            | 60      | LF   |        |   |
| 19     | (3-1/2") Sound attenuation insulation.   | 60      | SF   |        |   |
| 20     | (5/8", 1-Layer) Gyp. Bd. one side.       | 60      | SF   |        |   |
| 21     | (3-5/8") Top & bottom track.             | 10      | LF   |        |   |
| 22     | Acoustic sealant.                        | 5       | LF   |        |   |
| 23     | <b>TYPE 4, GWB WALL (77 LF)</b>          |         |      |        |   |
| 24     | (3-5/8") Metal stud @ 16" O.C            | 435     | LF   |        |   |
| 25     | (3-1/2") Sound attenuation insulation.   | 553     | SF   |        |   |
| 26     | (5/8", 1-Layer) Gyp. Bd. both side.      | 1,105   | SF   |        |   |
| 27     | (3-5/8") Top & bottom track.             | 154     | LF   |        |   |
| 28     | Acoustic sealant.                        | 56      | LF   |        |   |
| 29     | <b>TYPE 5, GWB WALL (19 LF)</b>          |         |      |        |   |
| 30     | (3-5/8") Metal stud @ 16" O.C            | 195     | LF   |        |   |
| 31     | (5/8", 1-Layer) Gyp. Bd. both side.      | 485     | SF   |        |   |
| 32     | (3-5/8") Top & bottom track.             | 38      | LF   |        |   |
| 33     | Acoustic sealant.                        | 19      | LF   |        |   |
| 34     | <b>TYPE 6, GWB WALL (3 LF)</b>           |         |      |        |   |
| 35     | (3-5/8") Metal stud @ 16" O.C            | 35      | LF   |        |   |
| 36     | (5/8", 1-Layer) Gyp. Bd. both side.      | 60      | SF   |        |   |
| 37     | (3-5/8") Top & bottom track.             | 6       | LF   |        |   |
| 38     | Acoustic sealant.                        | 6       | LF   |        |   |
| 39     | <b>TYPE 7, GWB WALL (14 LF)</b>          |         |      |        |   |
| 40     | (3-5/8") Metal stud @ 16" O.C            | 150     | LF   |        |   |
| 41     | (5/8", 1-Layer) Gyp. Bd. one side.       | 180     | SF   |        |   |
| 42     | (3-5/8") Top & bottom track.             | 28      | LF   |        |   |
| 43     | Acoustic sealant.                        | 14      | LF   |        |   |
| 44     | <b>TYPE 8, GWB WALL (2 LF)</b>           |         |      |        |   |
| 45     | (3-5/8") Metal stud @ 16" O.C            | 35      | LF   |        |   |
| 46     | (5/8", 1-Layer) Gyp. Bd. one side.       | 26      | SF   |        |   |
| 47     | (3-5/8") Top & bottom track.             | 4       | LF   |        |   |
| 48     | Acoustic sealant.                        | 2       | LF   |        |   |
| 49     | <b>TYPE 9, GWB WALL (24 LF)</b>          |         |      |        |   |
| 50     | (3-5/8") Metal stud @ 16" O.C            | 135     | LF   |        |   |

|     |  |     |    |  |  |
|-----|--|-----|----|--|--|
| 51  | (5/8", 1-Layer) Gyp. Bd. both side.    | 315 | SF |  |  |
| 52  | (3-5/8") Top & bottom track.           | 48  | LF |  |  |
| 53  | Acoustic sealant.                      | 14  | LF |  |  |
| 54  | <b>TYPE 10, GWB WALL (25 LF)</b>       |     |    |  |  |
| 55  | (3-5/8") Metal stud @ 16" O.C          | 205 | LF |  |  |
| 56  | (3-1/2") Sound attenuation insulation. | 250 | SF |  |  |
| 57  | (5/8", 1-Layer) Gyp. Bd. both side.    | 500 | SF |  |  |
| 58  | (3-5/8") Top & bottom track.           | 50  | LF |  |  |
| 59  | Acoustic sealant.                      | 34  | LF |  |  |
| 60  | <b>TYPE 11, GWB WALL (11 LF)</b>       |     |    |  |  |
| 61  | (3-5/8") Metal stud @ 16" O.C          | 120 | LF |  |  |
| 62  | (3-1/2") Sound attenuation insulation. | 145 | SF |  |  |
| 63  | (5/8", 1-Layer) Gyp. Bd. one side.     | 145 | SF |  |  |
| 64  | (3-5/8") Top & bottom track.           | 22  | LF |  |  |
| 65  | Acoustic sealant.                      | 11  | LF |  |  |
| 66  | <b>TYPE 12, GWB WALL (29 LF)</b>       |     |    |  |  |
| 67  | (3-5/8") Metal stud @ 16" O.C          | 200 | LF |  |  |
| 68  | (3-1/2") Sound attenuation insulation. | 245 | SF |  |  |
| 69  | (5/8", 1-Layer) Gyp. Bd. both side.    | 485 | SF |  |  |
| 70  | (3-5/8") Top & bottom track.           | 58  | LF |  |  |
| 71  | Acoustic sealant.                      | 30  | LF |  |  |
| 72  | <b>TYPE 13, GWB WALL (32 LF)</b>       |     |    |  |  |
| 73  | (3-5/8") Metal stud @ 16" O.C          | 320 | LF |  |  |
| 74  | (3-1/2") Sound attenuation insulation. | 410 | SF |  |  |
| 75  | (5/8", 1-Layer) Gyp. Bd. both side.    | 690 | SF |  |  |
| 76  | (3-5/8") Top & bottom track.           | 64  | LF |  |  |
| 77  | Acoustic sealant.                      | 64  | LF |  |  |
| 78  | <b>TYPE 14, GWB WALL (35 LF)</b>       |     |    |  |  |
| 79  | (3-5/8") Metal stud @ 16" O.C          | 355 | LF |  |  |
| 80  | (5/8", 1-Layer) Gyp. Bd. one side.     | 455 | SF |  |  |
| 81  | (3-5/8") Top & bottom track.           | 70  | LF |  |  |
| 82  | Acoustic sealant.                      | 35  | LF |  |  |
| 83  | <b>TYPE 15, GWB WALL (25 LF)</b>       |     |    |  |  |
| 84  | (3-5/8") Metal stud @ 16" O.C          | 250 | LF |  |  |
| 85  | (3-1/2") Sound attenuation insulation. | 320 | SF |  |  |
| 86  | (5/8", 1-Layer) Gyp. Bd. both side.    | 535 | SF |  |  |
| 87  | (3-5/8") Top & bottom track.           | 50  | LF |  |  |
| 88  | Acoustic sealant.                      | 50  | LF |  |  |
| 89  | <b>TYPE 16, GWB WALL (9 LF)</b>        |     |    |  |  |
| 90  | (3-5/8") Metal stud @ 16" O.C          | 100 | LF |  |  |
| 91  | (5/8", 1-Layer) Gyp. Bd. both side.    | 230 | SF |  |  |
| 92  | (3-5/8") Top & bottom track.           | 18  | LF |  |  |
| 93  | Acoustic sealant.                      | 18  | LF |  |  |
| 94  | <b>TYPE 17, GWB WALL (6 LF)</b>        |     |    |  |  |
| 95  | (3-5/8") Metal stud @ 16" O.C          | 65  | LF |  |  |
| 96  | (3-1/2") Sound attenuation insulation. | 70  | SF |  |  |
| 97  | (5/8", 1-Layer) Gyp. Bd. both side.    | 115 | SF |  |  |
| 98  | (3-5/8") Top & bottom track.           | 12  | LF |  |  |
| 99  | Acoustic sealant.                      | 12  | LF |  |  |
| 100 | <b>TYPE 18, GWB WALL (48 LF)</b>       |     |    |  |  |
| 101 | (3-5/8") Metal stud @ 16" O.C          | 480 | LF |  |  |
| 102 | (3-1/2") Sound attenuation insulation. | 620 | SF |  |  |
| 103 | (5/8", 1-Layer) Gyp. Bd. both side.    | 620 | SF |  |  |
| 104 | (3-5/8") Top & bottom track.           | 96  | LF |  |  |
| 105 | Acoustic sealant.                      | 48  | LF |  |  |
| 106 | <b>TYPE 19, GWB WALL (36 LF)</b>       |     |    |  |  |

|     |  |       |    |  |  |
|-----|--|-------|----|--|--|
| 107 | (3-5/8") Metal stud @ 16" O.C            | 400   | LF |  |  |
| 108 | (5/8", 1-Layer) Gyp. Bd. both side.      | 990   | SF |  |  |
| 109 | (3-5/8") Top & bottom track.             | 72    | LF |  |  |
| 110 | Acoustic sealant.                        | 72    | LF |  |  |
| 111 | <b>TYPE 20, GWB WALL (9 LF)</b>          |       |    |  |  |
| 112 | (3-5/8") Metal stud @ 16" O.C            | 190   | LF |  |  |
| 113 | (3-1/2") Sound attenuation insulation.   | 110   | SF |  |  |
| 114 | (5/8", 1-Layer) Gyp. Bd. both side.      | 220   | SF |  |  |
| 115 | (3-5/8") Top & bottom track.             | 36    | LF |  |  |
| 116 | Acoustic sealant.                        | 18    | LF |  |  |
| 117 | <b>TYPE 21, GWB WALL (61 LF)</b>         |       |    |  |  |
| 118 | (3-5/8") Metal stud @ 16" O.C            | 425   | LF |  |  |
| 119 | (3-1/2") Sound attenuation insulation.   | 535   | SF |  |  |
| 120 | (5/8", 1-Layer) Gyp. Bd. both side.      | 960   | SF |  |  |
| 121 | (3-5/8") Top & bottom track.             | 122   | LF |  |  |
| 122 | Acoustic sealant.                        | 22    | LF |  |  |
| 123 | <b>TYPE 22, GWB WALL (9 LF)</b>          |       |    |  |  |
| 124 | (3-5/8") Metal stud @ 16" O.C            | 115   | LF |  |  |
| 125 | (5/8", 1-Layer) Gyp. Bd. one side.       | 130   | SF |  |  |
| 126 | (3-5/8") Top & bottom track.             | 18    | LF |  |  |
| 127 | Acoustic sealant.                        | 9     | LF |  |  |
| 128 | <b>TYPE 23, GWB WALL (18 LF)</b>         |       |    |  |  |
| 129 | (3-5/8") Metal stud @ 16" O.C            | 210   | LF |  |  |
| 130 | (3-1/2") Sound attenuation insulation.   | 260   | SF |  |  |
| 131 | (5/8", 1-Layer) Gyp. Bd. one side.       | 170   | SF |  |  |
| 132 | (3-5/8") Top & bottom track.             | 36    | LF |  |  |
| 133 | Acoustic sealant.                        | 18    | LF |  |  |
| 134 | <b>TYPE 24, GWB WALL (33 LF)</b>         |       |    |  |  |
| 135 | (3-5/8") Metal stud @ 16" O.C            | 370   | LF |  |  |
| 136 | (3-1/2") Sound attenuation insulation.   | 475   | SF |  |  |
| 137 | (5/8", 1-Layer) Gyp. Bd. both side.      | 620   | SF |  |  |
| 138 | (3-5/8") Top & bottom track.             | 66    | LF |  |  |
| 139 | Acoustic sealant.                        | 66    | LF |  |  |
| 140 | <b>TYPE 25, GWB WALL (77 LF)</b>         |       |    |  |  |
| 141 | (3-5/8") Metal stud @ 16" O.C            | 820   | LF |  |  |
| 142 | (5/8", 1-Layer) Gyp. Bd. both side.      | 2,130 | SF |  |  |
| 143 | (3-5/8") Top & bottom track.             | 154   | LF |  |  |
| 144 | Acoustic sealant.                        | 144   | LF |  |  |
| 145 | <b>TYPE 26, GWB FURRING WALL (27 LF)</b> |       |    |  |  |
| 146 | (7/8") Hat channel @ 16" O.C             | 195   | LF |  |  |
| 147 | (5/8", 1-Layer) Gyp. Bd. one side.       | 1,065 | SF |  |  |
| 148 | (7/8") Top & bottom track.               | 54    | LF |  |  |
| 149 | Acoustic sealant.                        | 27    | LF |  |  |
| 150 | <b>TYPE 27, GWB FURRING WALL (15 LF)</b> |       |    |  |  |
| 151 | (3-5/8") Metal stud @ 16" O.C            | 155   | LF |  |  |
| 152 | (7/8") Hat channel @ 16" O.C             | 155   | LF |  |  |
| 153 | (5/8", 1-Layer) Gyp. Bd. both side.      | 380   | SF |  |  |
| 154 | (3-5/8") Top & bottom track.             | 30    | LF |  |  |
| 155 | (7/8") Top & bottom track.               | 30    | LF |  |  |
| 156 | Acoustic sealant.                        | 30    | LF |  |  |
| 157 | <b>TYPE 28, GWB WALL (40 LF)</b>         |       |    |  |  |
| 158 | (3-5/8") Metal stud @ 16" O.C            | 450   | LF |  |  |
| 159 | (3-1/2") Sound attenuation insulation.   | 580   | SF |  |  |
| 160 | (5/8", 1-Layer) Gyp. Bd. both side.      | 935   | SF |  |  |
| 161 | (3-5/8") Top & bottom track.             | 80    | LF |  |  |
| 162 | Acoustic sealant.                        | 80    | LF |  |  |

|     |  |       |    |  |
|-----|--|-------|----|--|
| 163 | <b>TYPE 29, GWB WALL (40 LF)</b>       |       |    |  |
| 164 | (6") Metal stud @ 16" O.C              | 450   | LF |  |
| 165 | (3-1/2") Sound attenuation insulation. | 580   | SF |  |
| 166 | (5/8", 1-Layer) Gyp. Bd. both side.    | 740   | SF |  |
| 167 | (6") Top & bottom track.               | 80    | LF |  |
| 168 | Acoustic sealant.                      | 80    | LF |  |
| 169 | <b>TYPE 30, GWB WALL (93 LF)</b>       |       |    |  |
| 170 | (3-5/8") Metal stud @ 16" O.C          | 430   | LF |  |
| 171 | (5/8", 1-Layer) Gyp. Bd. both side.    | 1,090 | SF |  |
| 172 | (3-5/8") Top & bottom track.           | 186   | LF |  |
| 173 | Acoustic sealant.                      | 8     | LF |  |
| 174 | <b>TYPE 31, GWB WALL (77 LF)</b>       |       |    |  |
| 175 | (3-5/8") Metal stud @ 16" O.C          | 835   | LF |  |
| 176 | (3-1/2") Sound attenuation insulation. | 1,070 | SF |  |
| 177 | (5/8", 1-Layer) Gyp. Bd. both side.    | 1,450 | SF |  |
| 178 | (3-5/8") Top & bottom track.           | 154   | LF |  |
| 179 | Acoustic sealant.                      | 154   | LF |  |
| 180 | <b>TYPE 32, GWB WALL (65 LF)</b>       |       |    |  |
| 181 | (3-5/8") Metal stud @ 16" O.C          | 440   | LF |  |
| 182 | (3-1/2") Sound attenuation insulation. | 560   | SF |  |
| 183 | (5/8", 1-Layer) Gyp. Bd. both side.    | 1,000 | SF |  |
| 184 | (3-5/8") Top & bottom track.           | 130   | LF |  |
| 185 | Acoustic sealant.                      | 46    | LF |  |
| 186 | <b>TYPE 33, GWB WALL (8 LF)</b>        |       |    |  |
| 187 | (3-5/8") Metal stud @ 16" O.C          | 105   | LF |  |
| 188 | (3-1/2") Sound attenuation insulation. | 120   | SF |  |
| 189 | (5/8", 1-Layer) Gyp. Bd. one side.     | 80    | SF |  |
| 190 | (3-5/8") Top & bottom track.           | 16    | LF |  |
| 191 | Acoustic sealant.                      | 8     | LF |  |
| 192 | <b>TYPE 34, GWB WALL (12 LF)</b>       |       |    |  |
| 193 | (3-5/8") Metal stud @ 16" O.C          | 145   | LF |  |
| 194 | (3-1/2") Sound attenuation insulation. | 170   | SF |  |
| 195 | (5/8", 1-Layer) Gyp. Bd. both side.    | 285   | SF |  |
| 196 | (3-5/8") Top & bottom track.           | 24    | LF |  |
| 197 | Acoustic sealant.                      | 24    | LF |  |
| 198 | <b>TYPE 35, GWB WALL (25 LF)</b>       |       |    |  |
| 199 | (3-5/8") Metal stud @ 16" O.C          | 180   | LF |  |
| 200 | (3-1/2") Sound attenuation insulation. | 225   | SF |  |
| 201 | (5/8", 1-Layer) Gyp. Bd. both side.    | 450   | SF |  |
| 202 | (3-5/8") Top & bottom track.           | 50    | LF |  |
| 203 | Acoustic sealant.                      | 25    | LF |  |
| 204 | <b>TYPE 36, GWB WALL (61 LF)</b>       |       |    |  |
| 205 | (3-5/8") Metal stud @ 16" O.C          | 310   | LF |  |
| 206 | (3-1/2") Sound attenuation insulation. | 385   | SF |  |
| 207 | (5/8", 1-Layer) Gyp. Bd. both side.    | 710   | SF |  |
| 208 | (3-5/8") Top & bottom track.           | 122   | LF |  |
| 209 | Acoustic sealant.                      | 20    | LF |  |
| 210 | <b>TYPE 37, GWB WALL (56 LF)</b>       |       |    |  |
| 211 | (3-5/8") Metal stud @ 16" O.C          | 465   | LF |  |
| 212 | (3-1/2") Sound attenuation insulation. | 605   | SF |  |
| 213 | (5/8", 1-Layer) Gyp. Bd. both side.    | 1,060 | SF |  |
| 214 | (3-5/8") Top & bottom track.           | 112   | LF |  |
| 215 | Acoustic sealant.                      | 72    | LF |  |
| 216 | <b>TYPE 38, GWB WALL (24 LF)</b>       |       |    |  |
| 217 | (3-5/8") Metal stud @ 16" O.C          | 85    | LF |  |
| 218 | (3-1/2") Sound attenuation insulation. | 107   | SF |  |

|     |  |     |     |  |  |
|-----|--|-----|-----|--|--|
| 219 | (5/8", 1-Layer) Gyp. Bd. both side.    | 215 | SF  |  |  |
| 220 | (3-5/8") Top & bottom track.           | 48  | LF  |  |  |
| 221 | <b>TYPE 39, GWB WALL (39 LF)</b>       |     |     |  |  |
| 222 | (3-5/8") Metal stud @ 16" O.C          | 355 | LF  |  |  |
| 223 | (3-1/2") Sound attenuation insulation. | 450 | SF  |  |  |
| 224 | (5/8", 1-Layer) Gyp. Bd. both side.    | 900 | SF  |  |  |
| 225 | (3-5/8") Top & bottom track.           | 78  | LF  |  |  |
| 226 | Acoustic sealant.                      | 62  | LF  |  |  |
| 227 | <b>TYPE 40, GWB WALL (22 LF)</b>       |     |     |  |  |
| 228 | (3-5/8") Metal stud @ 16" O.C          | 130 | LF  |  |  |
| 229 | (5/8", 1-Layer) Gyp. Bd. both side.    | 320 | SF  |  |  |
| 230 | (3-5/8") Top & bottom track.           | 44  | LF  |  |  |
| 231 | Acoustic sealant.                      | 44  | LF  |  |  |
| 232 | <b>UNDERCOUNTER GWB WALL (14 LF)</b>   |     |     |  |  |
| 233 | (2x6) Wood stud @ 16" O.C              | 30  | LF  |  |  |
| 234 | (5/8", 1-Layer) Gyp. Bd. both side.    | 70  | SF  |  |  |
| 235 | (2x6) Top & bottom track.              | 28  | LF  |  |  |
| 236 | <b>GWB CEILING</b>                     |     |     |  |  |
| 237 | (5/8", 1-Layer) GWB Ceiling.           | 785 | SF  |  |  |
| 238 | Misc                                   | 1   | LOT |  |  |
| 239 | Other _____                            |     |     |  |  |
| 240 | Other _____                            |     |     |  |  |
| 241 | Other _____                            |     |     |  |  |
| 242 | <b>TOTAL:</b>                          |     |     |  |  |